



Technical Requirements:

1. Please use the grease specified by our company (LF-2 or F-3).
2. The * in the drawing is the installation reference size, please follow the installation size requirements.
3. For details of size, please confirm with the delivery specification drawings.

LSS-40-XX-C-I

MODEL	U	T	W	Model	Reduction ratio	Rated torque at 2000r/min input		Permissible peak torque at start and stop		Permissible maximum value for average load		Permissible maximum momentary torque		Permissible maximum input rotational speed (Grease)	Permissible average input rotational speed (Grease)	Backlash	weight	Desian life
Wave generator-A φ14	φ14H7	16.3 ^{+0.1} ₀	5JS9/P9	40		Nm	kgfm	Nm	kgfm	Nm	kgfm	Nm	kgfm	r/min	r/min	Arc Sec	kg	Hour
Wave generator-A φ19	φ19H7	21.8 ^{+0.1} ₀	6JS9/P9															
Wave generator-A φ22	φ22H7	24.8 ^{+0.1} ₀	6JS9/P9											4000	3000	≤20	LSS-C:1.7	10000
		25.3 ^{+0.1} ₀	8JS9/P9															15000
						137	14	402	41	196	20	686	70					15000
						206	21	519	53	284	29	980	100					15000
						265	27	568	58	372	38	1080	110					15000
						294	30	617	63	451	46	1180	120					15000